

A		B		C		D		E		F		G		H																																																										
仅供参考												REV.		REVISION RECORD		DATE																																																								
												A0		新图面发行		2017. 06. 16																																																								
1												主要技术参数 Main Specifications						1																																																						
2												线 数 (Poles): 08~40 接触电阻 (Contact resistance): ≤20mΩ 绝缘电阻 (Insulation resistance): ≥1000MΩ 额定电压 (Rated voltage): 250V AC DC 额定电流 (Rated current): 3.0A AC DC 耐 电 压 (Withstand Voltage): 1000V AC/minute 温度范围 (Temperature Range) : -25℃~ +85℃						2																																																						
3																		3																																																						
4																		4																																																						
5												<table><tr><th rowspan="2">PIN</th><th colspan="2">Dimensions</th></tr><tr><th>A</th><th>B</th></tr><tr><td>2*4P</td><td>7.50</td><td>14.70</td></tr><tr><td>2*5P</td><td>10.00</td><td>17.20</td></tr><tr><td>2*6P</td><td>12.50</td><td>19.70</td></tr><tr><td>2*7P</td><td>15.00</td><td>22.20</td></tr><tr><td>2*8P</td><td>17.50</td><td>24.70</td></tr><tr><td>2*9P</td><td>20.00</td><td>27.20</td></tr><tr><td>2*10P</td><td>22.50</td><td>29.70</td></tr><tr><td>2*11P</td><td>25.00</td><td>32.20</td></tr><tr><td>2*12P</td><td>27.50</td><td>34.70</td></tr><tr><td>2*13P</td><td>30.00</td><td>37.20</td></tr><tr><td>2*14P</td><td>32.50</td><td>39.70</td></tr><tr><td>2*15P</td><td>35.00</td><td>42.20</td></tr><tr><td>2*16P</td><td>37.50</td><td>44.70</td></tr><tr><td>2*17P</td><td>40.00</td><td>47.20</td></tr><tr><td>2*18P</td><td>42.50</td><td>49.70</td></tr><tr><td>2*20P</td><td>47.50</td><td>54.70</td></tr></table>						PIN	Dimensions		A	B	2*4P	7.50	14.70	2*5P	10.00	17.20	2*6P	12.50	19.70	2*7P	15.00	22.20	2*8P	17.50	24.70	2*9P	20.00	27.20	2*10P	22.50	29.70	2*11P	25.00	32.20	2*12P	27.50	34.70	2*13P	30.00	37.20	2*14P	32.50	39.70	2*15P	35.00	42.20	2*16P	37.50	44.70	2*17P	40.00	47.20	2*18P	42.50	49.70	2*20P	47.50	54.70	5	
PIN	Dimensions																																																																							
	A	B																																																																						
2*4P	7.50	14.70																																																																						
2*5P	10.00	17.20																																																																						
2*6P	12.50	19.70																																																																						
2*7P	15.00	22.20																																																																						
2*8P	17.50	24.70																																																																						
2*9P	20.00	27.20																																																																						
2*10P	22.50	29.70																																																																						
2*11P	25.00	32.20																																																																						
2*12P	27.50	34.70																																																																						
2*13P	30.00	37.20																																																																						
2*14P	32.50	39.70																																																																						
2*15P	35.00	42.20																																																																						
2*16P	37.50	44.70																																																																						
2*17P	40.00	47.20																																																																						
2*18P	42.50	49.70																																																																						
2*20P	47.50	54.70																																																																						
6																		6																																																						
7																		7																																																						
8		<table><tr><td rowspan="4"></td><td colspan="2">GENERAL TOLERANCES</td><td rowspan="2">SCALE: 1:1</td><td rowspan="2">NAME</td><td rowspan="2">DATE</td><td rowspan="4"></td><td colspan="2">深圳市思拓展电子有限公司</td><td colspan="2" rowspan="4">PART. NO: ST-WF-250-007Y</td></tr><tr><td>LINEAR</td><td>ANGLES</td><td colspan="2">SHENZHEN SINOTOP ELECTRONICS CO., LTD</td></tr><tr><td>0.0±0.30</td><td>X° REF±6°</td><td>APPROVED</td><td></td><td colspan="2">公司网址: www.szstuo.cn 公司电话: 0755-23765350</td></tr><tr><td>UNIT: MM</td><td>0.00±0.20</td><td>X° ±3°</td><td>DESIGNER</td><td></td><td colspan="2">邮 箱: 2850175982@qq.com 公司传真: 0755-23765341</td></tr><tr><td>SIZE: A4</td><td>0.000±0.10</td><td>X° X'±2°</td><td>DRAWN</td><td>肖坤权</td><td>2017. 06. 16</td><td colspan="2">TITLE: 2.50mmPITCH HOUSING</td><td colspan="2">REV: A0</td><td colspan="2">SHEET: 1/1</td></tr></table>											GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE		深圳市思拓展电子有限公司		PART. NO: ST-WF-250-007Y		LINEAR	ANGLES	SHENZHEN SINOTOP ELECTRONICS CO., LTD		0.0±0.30	X° REF±6°	APPROVED		公司网址: www.szstuo.cn 公司电话: 0755-23765350		UNIT: MM	0.00±0.20	X° ±3°	DESIGNER		邮 箱: 2850175982@qq.com 公司传真: 0755-23765341		SIZE: A4	0.000±0.10	X° X'±2°	DRAWN	肖坤权	2017. 06. 16	TITLE: 2.50mmPITCH HOUSING		REV: A0		SHEET: 1/1								8														
	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE		深圳市思拓展电子有限公司		PART. NO: ST-WF-250-007Y																																																															
	LINEAR	ANGLES					SHENZHEN SINOTOP ELECTRONICS CO., LTD																																																																	
	0.0±0.30	X° REF±6°	APPROVED		公司网址: www.szstuo.cn 公司电话: 0755-23765350																																																																			
	UNIT: MM	0.00±0.20	X° ±3°	DESIGNER			邮 箱: 2850175982@qq.com 公司传真: 0755-23765341																																																																	
SIZE: A4	0.000±0.10	X° X'±2°	DRAWN	肖坤权	2017. 06. 16	TITLE: 2.50mmPITCH HOUSING		REV: A0		SHEET: 1/1																																																														
A		B		C		D		E		F		G		H																																																										